

1. IDENTIFICATION OF THE SUBSTANCE/MIXTURE AND OF THE COMPANY/UNDERTAKING

Ashland P.O. Box 2219 Columbus, OH 43216	Regulatory Information Number Telephone Emergency telephone number	1-800-325-3751 614-790-3333 1-800-ASHLAND (1-800-274- 5263)
Product name	PARTS PLUS ® HD SAE 30 PREM	IIUM MOTOR OIL
Product code Product Use Description	PP3371 No data	

2. HAZARDS IDENTIFICATION

Emergency Overview

Appearance: liquid

CAUTION! PROLONGED OR REPEATED CONTACT MAY DRY THE SKIN AND CAUSE IRRITATION AND BURNS.

Potential Health Effects

Exposure routes

Inhalation, Skin absorption, Skin contact, Eye Contact, Ingestion

Eye contact

Unlikely to cause eye irritation or injury.

Skin contact

May cause mild skin irritation. Symptoms may include redness and burning of skin. Prolonged or repeated contact may dry the skin. Symptoms may include redness, burning, and drying and cracking of skin, skin burns, and other skin damage.

Ingestion

Swallowing small amounts of this material during normal handling is not likely to cause harmful effects. Swallowing large amounts may be harmful.



Inhalation

It is possible to breathe this material under certain conditions of handling and use (for example, during heating, spraying, or stirring). Breathing small amounts of this material during normal handling is not likely to cause harmful effects. Breathing large amounts may be harmful. Symptoms are not expected at air concentrations below the recommended exposure limits, if applicable (see Section 8.).

Aggravated Medical Condition

Preexisting disorders of the following organs (or organ systems) may be aggravated by exposure to this material:, Skin, lung (for example, asthma-like conditions)

Symptoms

Signs and symptoms of exposure to this material through breathing, swallowing, and/or passage of the material through the skin may include:, acne, stomach or intestinal upset (nausea, vomiting, diarrhea), irritation (nose, throat, airways)

Target Organs

No data

Carcinogenicity

This material is not listed as a carcinogen by the International Agency for Research on Cancer (IARC), the National Toxicology Program (NTP), or the Occupational Safety and Health Administration (OSHA). Used motor oil has been shown to cause skin cancer in laboratory animals continually exposed by repeated applications. Avoid prolonged or repeated skin contact.

Reproductive hazard

There are no data available for assessing risk to the fetus from maternal exposure to this material.

3. COMPOSITION/INFORMATION ON INGREDIENTS

Hazardous Components	CAS-No.	Concentration	
HEAVY PARAFFINIC DISTILLATE	64742-54-7	>=50-<60%	_
HEAVY PARAFFINIC DISTILLATE	64742-54-7	>=40-<50%	

4. FIRST AID MEASURES



Eyes

If symptoms develop, move individual away from exposure and into fresh air. Flush eyes gently with water while holding eyelids apart. If symptoms persist or there is any visual difficulty, seek medical attention.

Skin

Remove contaminated clothing. Wash exposed area with soap and water. If symptoms persist, seek medical attention. Launder clothing before reuse.

Ingestion

Seek medical attention. If individual is drowsy or unconscious, do not give anything by mouth; place individual on the left side with the head down. Contact a physician, medical facility, or poison control center for advice about whether to induce vomiting. If possible, do not leave individual unattended.

Inhalation

If symptoms develop, move individual away from exposure and into fresh air. If symptoms persist, seek medical attention. If breathing is difficult, administer oxygen. Keep person warm and quiet; seek immediate medical attention.

Notes to physician

Hazards: Acute aspiration of large amounts of oil-laden material may produce a serious aspiration pneumonia. Patients who aspirate these oils should be followed for the development of long-term sequelae. Repeated aspiration of small quantities of mineral oil can produce chronic inflammation of the lungs (i.e. lipoid pneumonia) that may progress to pulmonary fibrosis. Symptoms are often subtle and radiological changes appear worse than clinical abnormalities. Occasionally, persistent cough, irritation of the upper respiratory tract, shortness of breath with exertion, fever, and bloody sputum occur. Inhalation exposure to oil mists below current workplace exposure limits is unlikely to cause pulmonary abnormalities.

Treatment: No information available.

5. FIRE-FIGHTING MEASURES

Suitable extinguishing media

Dry chemical, Carbon dioxide (CO2), Water spray

Hazardous combustion products

carbon dioxide and carbon monoxide, Hydrocarbons



Precautions for fire-fighting

Wear full firefighting turn-out gear (full Bunker gear), and respiratory protection (SCBA). DO NOT direct a solid stream of water or foam into hot, burning pools of liquid since this may cause frothing and increase fire intensity. Frothing can be violent and possibly endanger any firefighter standing too close to the burning liquid. Use water spray to cool fire exposed containers and structures until fire is out if it can be done with minimal risk. Avoid spreading burning material with water used for cooling purposes.

NFPA Flammable and Combustible Liquids Classification

Combustible Liquid Class IIIB

6. ACCIDENTAL RELEASE MEASURES

Personal precautions

For personal protection see section 8. Persons not wearing protective equipment should be excluded from area of spill until clean-up has been completed.

Environmental precautions

Prevent spreading over a wide area (e.g. by containment or oil barriers). Do not let product enter drains. Do not flush into surface water or sanitary sewer system.

Methods for cleaning up

Keep in suitable, closed containers for disposal. Soak up with inert absorbent material (e.g. sand, silica gel, acid binder, universal binder, sawdust).

Other information

Comply with all applicable federal, state, and local regulations.

7. HANDLING AND STORAGE

Handling

Containers of this material may be hazardous when emptied. Since emptied containers retain product residues (vapor, liquid, and/or solid), all hazard precautions given in the data sheet must be observed.

Storage

Store in a cool, dry, ventilated area.

Page 4 / 11



Page: 5 Revision Date: 09/09/2010 Print Date: 12/17/2010 MSDS Number: R0178048 Version: 3.0

PARTS PLUS ® HD SAE 30 PREMIUM MOTOR OIL PP3371

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Exposure Guidelines

General advice

These recommendations provide general guidance for handling this product. Personal protective equipment should be selected for individual applications and should consider factors which affect exposure potential, such as handling practices, chemical concentrations and ventilation. It is ultimately the responsibility of the employer to follow regulatory guidelines established by local authorities.

Exposure controls

Provide sufficient mechanical (general and/or local exhaust) ventilation to maintain exposure below exposure guidelines (if applicable) or below levels that cause known, suspected or apparent adverse effects.

Eye protection

Not required under normal conditions of use. Wear splash-proof safety goggles if material could be misted or splashed into eyes.

Skin and body protection

Wear normal work clothing including long pants, long-sleeved shirts and foot covering to prevent direct contact of the product with the skin. Launder clothing before reuse. If skin irritation develops, contact your facility health and safety professional or your local safety equipment supplier to determine the proper personal protective equipment for your use.

Wear resistant gloves (consult your safety equipment supplier).

Respiratory protection

A NIOSH-approved air-purifying respirator with an appropriate cartridge and/or filter may be permissible under certain circumstances where airborne concentrations are expected to exceed exposure limits (if applicable) or if overexposure has otherwise been determined. Protection provided by airpurifying respirators is limited. Use a positive pressure, air-supplied respirator if there is any potential for uncontrolled release, exposure levels are not known or any other circumstances where an airpurifying respirator may not provide adequate protection.

9. PHYSICAL AND CHEMICAL PROPERTIES

Physical state

liquid

Page 5 / 11



Page: 6 Revision Date: 09/09/2010 Print Date: 12/17/2010 MSDS Number: R0178048 Version: 3.0

PARTS PLUS ® HD SAE 30 PREMIUM MOTOR OIL PP3371

Form	no data available
Colour	no data available
Odour	no data available
Boiling point/boiling range	no data available
Melting point/range	no data available
Sublimation point	no data available
рН	no data available
Flash point	(>)390 °F / 199 °C Cleveland open cup
Ignition temperature	no data available
Evaporation rate	no data available
Lower explosion limit/Upper explosion limit	1 %(V) / 6 %(V)
Particle size	no data available
Vapour pressure	0.013 hPa @ 70.00 °F / 21.11 °C Calculated Vapor
	Pressure
Relative vapour density	no data available
Density	0.8785 g/cm3 @ 60.1 °F / 15.6 °C
Bulk density	No data
Water solubility	no data available
Solubility	no data available
Partition coefficient: n-octanol/water	no data available
log Pow	no data available
Autoignition temperature	no data available
Viscosity, dynamic	no data available
Viscosity, kinematic	no data available
Solids in Solution	no data available
Decomposition temperature	no data available
Burning number	no data available
Dust explosion constant	no data available
Minimum ignition energy	no data available

10. STABILITY AND REACTIVITY

Stability

Stable.

Conditions to avoid None known.

Incompatible products

Page 6 / 11



Page: 7 Revision Date: 09/09/2010 Print Date: 12/17/2010 MSDS Number: R0178048 Version: 3.0

PARTS PLUS ® HD SAE 30 PREMIUM MOTOR OIL PP3371

Strong oxidizing agents

Hazardous decomposition products

carbon dioxide and carbon monoxide, Hydrocarbons

Hazardous reactions

Product will not undergo hazardous polymerization.

Thermal decomposition

No data

11. TOXICOLOGICAL INFORMATION

Acute oral toxicity HEAVY PARAFFINIC DISTILLATE	: LD 50 Rat: > 15 g/kg
HEAVY PARAFFINIC DISTILLATE	: LD 50 Rat: >15 g/kg
Acute inhalation toxicity HEAVY PARAFFINIC DISTILLATE HEAVY PARAFFINIC DISTILLATE	no data availableno data available
Acute dermal toxicity HEAVY PARAFFINIC DISTILLATE	: LD 50 Rabbit:
HEAVY PARAFFINIC DISTILLATE	 > 5 g/kg : LD 50 Rabbit: > 5 g/kg

12. ECOLOGICAL INFORMATION

Biodegradability

HEAVY PARAFFINIC DISTILLATE : no data available



Page: 8 Revision Date: 09/09/2010 Print Date: 12/17/2010 MSDS Number: R0178048 Version: 3.0

HEAVY PARAFFINIC DISTILLATE	:	no data available
Bioaccumulation HEAVY PARAFFINIC DISTILLATE	:	no data available
HEAVY PARAFFINIC DISTILLATE	:	no data available
Ecotoxicity effects		
Toxicity to fish HEAVY PARAFFINIC DISTILLATE	:	no data available
HEAVY PARAFFINIC DISTILLATE	:	no data available
Toxicity to daphnia and other aquatic invertebra	tes.	
HEAVY PARAFFINIC DISTILLATE	:	no data available
HEAVY PARAFFINIC DISTILLATE	:	no data available
Toxicity to algae		
HEAVY PARAFFINIC DISTILLATE	:	no data available
HEAVY PARAFFINIC DISTILLATE	:	no data available
Toxicity to bacteria		
HEAVY PARAFFINIC DISTILLATE	:	no data available
HEAVY PARAFFINIC DISTILLATE	:	no data available
Biochemical Oxygen Demand (BOD)		
HEAVY PARAFFINIC DISTILLATE	:	no data available
HEAVY PARAFFINIC DISTILLATE	:	no data available
Chemical Oxygen Demand (COD)		
HEAVY PARAFFINIC DISTILLATE	:	no data available
HEAVY PARAFFINIC DISTILLATE		no data available



Page: 9 Revision Date: 09/09/2010 Print Date: 12/17/2010 MSDS Number: R0178048 Version: 3.0

PARTS PLUS ® HD SAE 30 PREMIUM MOTOR OIL PP3371

Additional ecological information HEAVY PARAFFINIC DISTILLATE

HEAVY PARAFFINIC DISTILLATE

: no data available

: no data available

13. DISPOSAL CONSIDERATIONS

Waste disposal methods

Dispose of in accordance with all applicable local, state and federal regulations. For assistance with your waste management needs - including disposal, recycling and waste stream reduction, contact Ashland Distribution's Environmental Services Group at 800-637-7922.

14. TRANSPORT INFORMATION

REGULATION

11000011101	•				
ID	PROPER SHIPPING NAME	*HAZARD	SUBSIDIARY	PACKING	MARINE
NUMBER		CLASS	HAZARDS	GROUP	POLLUTANT
					/ LTD. QTY.
U.S. DOT - ROAD					

Not dangerous goods

U.S. DOT - RAIL

Not dangerous goods

U.S. DOT - INLAND WATERWAYS

Not dangerous goods

TRANSPORT CANADA - ROAD

Not dangerous goods

TRANSPORT CANADA - RAIL

Not dangerous goods

TRANSPORT CANADA - INLAND WATERWAYS

Not dangerous goods

INTERNATIONAL MARITIME DANGEROUS GOODS

Page 9 / 11



Not dangerous goods

INTERNATIONAL AIR TRANSPORT ASSOCIATION - CARGO

Not dangerous goods

INTERNATIONAL AIR TRANSPORT ASSOCIATION - PASSENGER Not dangerous goods

MEXICAN REGULATION FOR THE LAND TRANSPORT OF HAZARDOUS MATERIALS AND WASTES

Not dangerous goods

*ORM = ORM-D, CBL = COMBUSTIBLE LIQUID

Dangerous goods descriptions (if indicated above) may not reflect quantity, end-use or region-specific exceptions that can be applied. Consult shipping documents for descriptions that are specific to the shipment.

15. REGULATORY INFORMATION

California Prop. 65

Proposition 65 warnings are not required for this product based	
on the results of a risk assessment.	

SARA Hazard Classification

No SARA Hazards

SARA 313: This material does not contain any chemical components with known CAS numbers that exceed the threshold (De Minimis) reporting levels established by SARA Title III, Section 313.

New Jersey RTK Label Information	
HEAVY PARAFFINIC DISTILLATE	64742-54-7
HEAVY PARAFFINIC DISTILLATE	64742-54-7
POLYOLEFIN AMIDE ALKENEAMINE	
LUBRICANT ADDITIVE	

Pennsylvania RTK Label Information	
------------------------------------	--

HEAVY PARAFFINIC DISTILLATE	64742-54-7
HEAVY PARAFFINIC DISTILLATE	64742-54-7



Page: 11 Revision Date: 09/09/2010 Print Date: 12/17/2010 MSDS Number: R0178048 Version: 3.0

PARTS PLUS ® HD SAE 30 PREMIUM MOTOR OIL PP3371

Notification status

US. Toxic Substances Control Act y	y (positive listing)
Canada. Canadian Environmental Protection Act (CEPA). y	y (positive listing)
Domestic Substances List (DSL). (Can. Gaz. Part II, Vol. 133)	
Australia. Industrial Chemical (Notification and Assessment) y	y (positive listing)
Act	
5 77 1 5	y (positive listing)
by ERMA New Zealand	/ · · · ·
1	e (special case)
	y (positive listing)
11 5	y (positive listing)
Waste Control Act	
China. Inventory of Existing Chemical Substances q	q (quantity restricted)

	HMIS	NFPA
Health	1	1
Flammability	1	1
Physical hazards	0	
Instability		0
Specific Hazard		

16. OTHER INFORMATION

The information accumulated herein is believed to be accurate but is not warranted to be whether originating with the company or not. Recipients are advised to confirm in advance of need that the information is current, applicable, and suitable to their circumstances. This MSDS has been prepared by Ashland's Environmental Health and Safety Department (1-800-325-3751).